

Полнолицевые маски С 702/TWIN, С 701, С 607/F

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eut@nt-rt.ru || сайт: <https://ekastu.nt-rt.ru>

Technical Data Sheet

C 702/TWIN

Order no.:	466 888	
Product designation:	Full Face Mask C 702/TWIN (Class 3) olive/black	
Applied standard:	DIN EN 136 (DIN = German Institute for Standardization)	
Utilization:	In connection with respiratory filter of the series 200 (special thread 66mm) as filtering device. The scope of protection is determined by the product information, technical standards and valid application rules.	
Description:	Faceblank enclose the entire face.	
Materials:	Faceblank	TPR (Thermoplastic Rubber)
	Head harness	EPDM (Ethylene-Propylene-Diene-Mixture)
	Inner mask	TPR (Thermoplastic Rubber)
	Disk-Frame	Polyamide
	Lens	Polycarbonate
	Inhalation valve	Silicone
	Connector	Fiberglass reinforced polyamide
	Connector-Clip	Fiberglass reinforced polyamide
Weight:	approx. 620 g	
Inhalation resistance:	at 30 l/min, constant flow max. 0.5 mbar (EN 136) at 95 l/min, constant flow max. 1.5 mbar (EN 136) at 160 l/min, constant flow max. 2.5 mbar (EN 136)	
Exhalation resistance:	at 160 l/min, constant flow max. 3.0 mbar (EN 136)	
Marking:	Trade mark of manufacturer (LOGO) Product designation Applied standard Manufacture year and -month CE-Identification Notified body Type identifying marking	
Handling:	Take the Full face mask from the Packing and/or Storage container directly before use. Use the Full face mask in accordance with the information brochure.	
Storage conditions:	Ambient temperature. Protect against cold, heat and humidity. Consider conditions noted on the packaging.	
Warning reference:	Please consider the information brochure!	
User references:	EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 'Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines'.	



Order no.: 466 701

Product designation:

Full Face Mask C 701 (Class 3) olive/black

In connection with respiratory filter (standard thread EN 148-1) as filtering device - directly or by means of breathing assistance AIRMATIC.
The scope of protection is determined by the product information, technical standards and valid application rules.



DESCRIPTION

Innovative inspiration system with rectangular inhalation valve and absence of non-return valves, which ensures excellent anti-fog, assuring a minimum level of breathing resistance

Panoramic visor, optical class 1 (EN 166), ensures a wide field of vision, without optical distortions

- Ballistic resistance (STANAG 2920)

Inner half mask and faceblank in thermoplastic

- Excellent adaptability to different facial conformation
- Hypoallergenic material

Comfortable harness fixed on 5 points made of EPDM

Approved for firefighters

MAIN FEATURES



PERFORMANCES



Sturdiness



Comfort



Panoramic view



Ergonomics



Easy maintenance

APPLICATION FIELDS



Marine



Industry



Hospital



Chemical Pharmaceutical
Industry



Agriculture

MATERIALS

- Face seal: Thermoplastic rubber (TPR)
- Inner half mask: Thermoplastic rubber (TPR)
- Disk-Frame: Polyamide (PA)
- Visor: Polycarbonate (PC)
- Inhalation valve: Silicone
- Connector: Polyamide (PA)
- Connector-Clip: Polyamide (PA)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)

WEIGHT

- approx. 620 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Full face mask from the Packing and/or Storage container directly before use
- Use the Full face mask in accordance with the information brochure

STORAGE

- Ambient temperature. Protect against cold, heat and humidity
- Consider conditions noted on the packaging
- Not higher than 50°C

CERTIFICATIONS

- The mask is certified as class 3 according to EN 136 (maximum mechanical, heat and flame resistance)
- For use with particle, gas and combined filters equipped with EN 148/1 threaded connection
- Certified according to European Regulation (EU) 2016/425

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.



Order no.: 466 607

Product designation:

Full Face Mask C 607/F (Class 3)

In connection with respiratory filter (standard thread DIN EN 148-1) as filtering device, in connection with powered filtering device as filtering device, in connection with compressed air line device as breathing apparatus and in connection with unassisted fresh air hose breathing device as breathing apparatus.
The scope of protection is determined by the product information, technical standards and valid application rules.



DESCRIPTION

- **Compact full face mask**, fitting any face conformations
- Polycarbonate visor with high impact resistance to acids, even at high concentrations
- Excellent voice transmission thanks to the frontal position of the speech diaphragm
- Resistance to flame and radiant heat: the mask is self-extinguishing and retains its protective capacity even after such severe tests. (approved according to DIN 58646/10)
- Quick donning and doffing; the shoulder strap allows to keep the mask ready for immediate use
- Easy maintenance, washing and disinfection. All components can be disassembled without special tools
- Approved for firefighters

MAIN FEATURES



Five straps elastic harness made of EPDM, with quick release buckles

Wide field of vision and distortion free visor made of polycarbonate, with fiberglass reinforced synthetic resin frame, easily replaceable

Inner mask with 2 check valves which reduce clearance volume and prevent the visor shield from misting up through even visor ventilation

Facepiece consists of non-irritating EPDM which is resistant to ageing and guarantees outstanding mechanical and chemical resistance

2 large exhalation valves with exhalation valve pre-chamber results in low Exhalation resistance and prevents dangerous media from penetrating the inside of the mask

Threaded connector conforming with European EN 148/1 standard, with speech diaphragm

PERFORMANCES



Sturdiness



Comfort



Panoramic view



Ergonomics



Easy maintenance

APPLICATION FIELDS



Marine



Industry



Hospital



Chemical Pharmaceutical Industry



Agriculture

MATERIALS

- Face seal: Ethylene-Propylene-Diene-Mixture (EPDM)
- Inner half mask: Ethylene-Propylene-Diene-Mixture (EPDM)
- Disk-Frame: Polyphenylene oxide (PPO)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)
- Visor: Polycarbonate (PC)
- Heat conduction plate: Metal
- Check valve: Rubber
- Inhalation valve: Rubber
- Exhalation valve: Rubber
- Exhalation valve cap: Polyphenylene oxide (PPO)
- Connector: Polyamide (PA)
- Connector-Clip: Metal
- Speech diaphragm: Metal

WEIGHT

- approx. 565 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Full face mask from the Packing and/or Storage container directly before use
- Use the Full face mask in accordance with the information brochure

STORAGE

- Ambient temperature. Protect against cold, heat and humidity
- Consider conditions noted on the packaging

CERTIFICATIONS

- The mask is certified as class 3 according to EN 136 (maximum mechanical, heat and flame resistance)
- For use with particle, gas and combined filters equipped with EN 148/1 threaded connection
- Certified according to European Regulation (EU) 2016/425

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eut@nt-rt.ru || сайт: <https://ekastu.nt-rt.ru>