

# Защитные очки и комплекты CARINA KLEIN DESIGN EXTASE

## Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: [eut@nt-rt.ru](mailto:eut@nt-rt.ru) || сайт: <https://ekastu.nt-rt.ru>



## Technical Data Sheet

## EXTASE clear

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                       |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Order no.:</b>           | 277 373                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                       |
| <b>Product designation:</b> | Safety Spectacle EXTASE clear                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                       |
| <b>Applied standard:</b>    | DIN EN 166 / DIN EN 170 (DIN = German Institute for Standardization)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                       |
| <b>Utilization:</b>         | The safety spectacle is ideal for factory visitors, laboratory workers and assembly workers. It can be carried in connection with half masks or filtering half masks. The scope of protection is determined by the product information, technical standards and valid application rules.                                                                                                                                                                                                                                                                                                  |                                                                                       |
| <b>Description:</b>         | The safety spectacle encloses the eye range.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                       |
| <b>Materials:</b>           | Frame<br>Nose pad upholstery<br>Temple upholstery<br>Mounting screw<br>Lens                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Polycarbonate<br>Polyvinyl chloride<br>Thermoplastic rubber<br>Metal<br>Polycarbonate |
| <b>Colour of frame:</b>     | silver-grey / green                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                       |
| <b>Lens thickness:</b>      | 1,3 mm – 2,3 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                       |
| <b>Lenses colour:</b>       | clear                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                       |
| <b>Weight:</b>              | approx. 33 g                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                       |
| <b>Marking:</b>             | Trade mark of manufacturer (LOGO)<br>Product designation<br>Applied standard<br>CE-Identification<br>Optical class<br>Operating range<br>Protection level of the eyeglass filters<br>Abbreviation for mechanical firmness                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>Marking explanation:</b> | 1 Optical class (particularly high requirement of the visual efficiency)<br>2-1.2 Protection level of the eyeglass filters (ultraviolet protection filter)<br>FT Mechanical firmness – Impact with high speed and low energy at extreme temperatures (-5°C to 55°C)                                                                                                                                                                                                                                                                                                                       |                                                                                       |
| <b>Properties:</b>          | Anti-Scratch<br>Anti-Fog<br>100,00% UV-Protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                       |
| <b>Handling:</b>            | Take the Safety spectacles from the packing directly before use.<br>Use the Safety spectacles in accordance with the information brochure.                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                       |
| <b>Storage conditions:</b>  | Ambient temperature. Protect against cold, heat and humidity.<br>Consider conditions noted on the information brochure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                       |
| <b>Warning reference:</b>   | Please consider the information brochure!                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>User references:</b>     | EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the ocular protection and facial protection with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-192 'use of ocular protection and facial protection'. |                                                                                       |

## Technical Data Sheet

## EXTASE tinted

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                       |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Order no.:</b>           | 277 375                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                       |
| <b>Product designation:</b> | Safety Spectacle EXTASE tinted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                       |
| <b>Applied standard:</b>    | DIN EN 166 / DIN EN 172 (DIN = German Institute for Standardization)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                       |
| <b>Utilization:</b>         | The safety spectacle is ideal for work in the outdoor area with sunlight irradiation.<br>It can be carried in connection with half masks or filtering half masks.<br>The scope of protection is determined by the product information, technical standards and valid application rules.                                                                                                                                                                                                                                                                                                      |                                                                                       |
| <b>Description:</b>         | The safety spectacle encloses the eye range.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>Materials:</b>           | Frame<br>Nose pad upholstery<br>Temple upholstery<br>Mounting screw<br>Lens                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Polycarbonate<br>Polyvinyl chloride<br>Thermoplastic rubber<br>Metal<br>Polycarbonate |
| <b>Colour of frame:</b>     | silver-grey / green                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                       |
| <b>Lens thickness:</b>      | 1,3 mm – 2,3 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                       |
| <b>Lenses colour:</b>       | dark grey (reflective)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                       |
| <b>Weight:</b>              | approx. 33 g                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>Marking:</b>             | Trade mark of manufacturer (LOGO)<br>Product designation<br>Applied standard<br>CE-Identification<br>Optical class<br>Operating range<br>Protection level of the eyeglass filters<br>Abbreviation for mechanical firmness                                                                                                                                                                                                                                                                                                                                                                    |                                                                                       |
| <b>Marking explanation:</b> | 1      Optical class (particularly high requirement of the visual efficiency)<br>5-3.1      Protection level of the eyeglass filters (ultraviolet protection filter)<br>FT      Mechanical firmness – Impact with high speed and low energy at extreme temperatures (-5°C to 55°C)                                                                                                                                                                                                                                                                                                           |                                                                                       |
| <b>Properties:</b>          | Anti-Scratch<br>Anti-Fog<br>100,00% UV-Protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                       |
| <b>Handling:</b>            | Take the Safety spectacles from the packing directly before use.<br>Use the Safety spectacles in accordance with the information brochure.                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                       |
| <b>Storage conditions:</b>  | Ambient temperature. Protect against cold, heat and humidity.<br>Consider conditions noted on the information brochure.                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                       |
| <b>Warning reference:</b>   | Please consider the information brochure!                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                       |
| <b>User references:</b>     | EKASTU Safety GmbH guarantees the indicated achievement according to class and type.<br>It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the ocular protection and facial protection with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-192 'use of ocular protection and facial protection'. |                                                                                       |



# Safety Spectacle-Set CARINA KLEIN DESIGN™ EXTASE



The sporty designer safety spectacles for professionals, fully comply with DIN EN 166, as well as DIN EN 170 and additionally DIN EN 172 (EXTASE tinted).

consisting of:

- 1 Safety Spectacle CARINA KLEIN DESIGN™ EXTASE, clear
- 1 Safety Spectacle CARINA KLEIN DESIGN™ EXTASE, tinted
- 1 mobile spectacle pouch CARINA KLEIN DESIGN™
- 1 cord for spectacles CARINA KLEIN DESIGN™
- **For FREE 1 antifogging and cleaning spray• for at least 250 applications**

Features of both safety spectacles:

- maximum wearing comfort with unrestricted field of vision
- soft, formed nose pad
- pleasant, soft and non-slip temple construction
- fashionable and sporty design
- anti-scratch coating (super anti-scratch)
- fog-free (super anti-fog)
- 100,00% UV protection thanks to innovative UV 400 technology
- crystal-clear lenses with optimum side protection
- **can be used in many work areas for a wide variety of activities (also suitable for leisure use)**

## По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04  
Ангарск (3955)60-70-56  
Архангельск (8182)63-90-72  
Астрахань (8512)99-46-04  
Барнаул (3852)73-04-60  
Белгород (4722)40-23-64  
Благовещенск (4162)22-76-07  
Брянск (4832)59-03-52  
Владивосток (423)249-28-31  
Владикавказ (8672)28-90-48  
Владимир (4922)49-43-18  
Волгоград (844)278-03-48  
Вологда (8172)26-41-59  
Воронеж (473)204-51-73  
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06  
Ижевск (3412)26-03-58  
Иркутск (395)279-98-46  
Казань (843)206-01-48  
Калининград (4012)72-03-81  
Калуга (4842)92-23-67  
Кемерово (3842)65-04-62  
Киров (8332)68-02-04  
Коломна (4966)23-41-49  
Кострома (4942)77-07-48  
Краснодар (861)203-40-90  
Красноярск (391)204-63-61  
Курск (4712)77-13-04  
Курган (3522)50-90-47  
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13  
Москва (495)268-04-70  
Мурманск (8152)59-64-93  
Набережные Челны (8552)20-53-41  
Нижний Новгород (831)429-08-12  
Новокузнецк (3843)20-46-81  
Ноябрьск (3496)41-32-12  
Новосибирск (383)227-86-73  
Омск (3812)21-46-40  
Орел (4862)44-53-42  
Оренбург (3532)37-68-04  
Пенза (8412)22-31-16  
Петрозаводск (8142)55-98-37  
Псков (8112)59-10-37  
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15  
Рязань (4912)46-61-64  
Самара (846)206-03-16  
Санкт-Петербург (812)309-46-40  
Саратов (845)249-38-78  
Севастополь (8692)22-31-93  
Саранск (8342)22-96-24  
Симферополь (3652)67-13-56  
Смоленск (4812)29-41-54  
Сочи (862)225-72-31  
Ставрополь (8652)20-65-13  
Сургут (3462)77-98-35  
Сыктывкар (8212)25-95-17  
Тамбов (4752)50-40-97  
Тверь (4822)63-31-35

Тольятти (8482)63-91-07  
Томск (3822)98-41-53  
Тула (4872)33-79-87  
Тюмень (3452)66-21-18  
Ульяновск (8422)24-23-59  
Улан-Удэ (3012)59-97-51  
Уфа (347)229-48-12  
Хабаровск (4212)92-98-04  
Чебоксары (8352)28-53-07  
Челябинск (351)202-03-61  
Череповец (8202)49-02-64  
Чита (3022)38-34-83  
Якутск (4112)23-90-97  
Ярославль (4852)69-52-93

**Россия** +7(495)268-04-70

**Казахстан** +(727)345-47-04

**Беларусь** +(375)257-127-884

**Узбекистан** +998(71)205-18-59

**Киргизия** +996(312)96-26-47

эл.почта: [eut@nt-rt.ru](mailto:eut@nt-rt.ru) || сайт: <https://ekastu.nt-rt.ru>